



LINE AND LOAD  
TERM. THREAD  
#12-24 UNC

TORQUE WIRE CONNECTOR  
SCREW TO: 40 LB-IN.

Ø .203  
2 MTG. HOLES  
(FOR 10-32  
SCREWS)

USE #1/0 COPPER  
OR ALUMINUM WIRE

TORQUE TERMINAL SCREW  
WITH LUG 55 LB-IN.

TORQUE TERMINAL SCREW  
WITH FUSE CLIP 55 LB-IN.

1.00 DURING  
HANDLE ROTATION

**Rockwell  
Automation**

1494U, 60 AMP SWITCH DIM DRAWING

CONFIDENTIAL AND PROPRIETARY INFORMATION.  
THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY  
INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY  
NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT  
WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL  
AUTOMATION, INC.

Sheet 1 Of 1

Drawn by: LEQUENTI

Date: JUL-16-2014

Size		Ver
<b>B</b>	<b>10001235007</b>	<b>00</b>

SCALE 0.485

10001235006.ASM