




Screw Connection Terminal Blocks

Grounding Blocks

	1492-JG70				1492-JG120			1492-JDG3				
<p>Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.</p> 												
Specifications	<i>Feed-through grounding terminal block</i>				<i>Feed-through grounding terminal block</i>			<i>Two-circuit terminal block with one feed-through and one grounding circuit</i>				
Certifications												
Voltage Rating	—				—			300V AC/DC		400V AC/DC		
Maximum Current	Grounding				—			20 A		24 A		
Wire Range (Rated Cross Section)	#6...2/0 AWG		70 mm ² (#8...2/0 AWG)		#4...3/0 AWG		#4...4/0 AWG	16...95 mm ²		#22...12 AWG		
Wire Strip Length	0.87 in. (22 mm)				1.06 in. (27 mm)			0.39 in. (10 mm)				
Recommended Tightening Torque	87.0 lb•in (9.8 N•m)				88.5 lb•in (10 N•m)			4.5...7.1 lb•in. (0.5...0.8 N•m)				
Mounting Torque — Center Screw	17.7...35.4 lb•in (2.0...4.0 N•m)				—			—				
Density	14 pcs/ft (48 pcs/m)				11 pcs/ft (37 pcs/m)			59 pcs/ft (196 pcs/m)				
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				
Short-Circuit Current Rating	See page 12-42											
Terminal Blocks	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Color:	Green/Yellow		1492-JG70		10		1492-JG120		5		—	
	Grey		—		—		—		—		1492-JDG3	
	Grey		—		—		—		—		100	
Accessories	Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.		Cat. No.		Pkg Qty.	
Mounting Rails:	—		—		—		—		199-DR1		10	
1 m Symmetrical DIN (Steel)	—		—		—		—		1492-DR5		10	
1 m Symmetrical DIN (Aluminum)	—		—		—		—		1492-DR6		2	
1 m Hi-Rise Sym. DIN (Aluminum)	—		—		—		—		1492-DR7		2	
1 m Angled Hi-Rise Sym. DIN (Steel)	—		—		—		—		—		—	
Screw Type 1 m Symmetrical Heavy Duty DIN (Copper, Unslotted)	1492-DR8		5		1492-DR8		5		—		—	
End Barrier	Grey		Not Required		—		—		1492-EBJD3		20	
	Yellow		Not Required		—		—		1492-EBJD3-Y		20	
Jumpers:	—		—		—		—		1492-CJJ5-10		20	
Screw Center Jumper — 10-pole	—		—		—		—		1492-CJJ5-4		50	
Screw Center Jumper — 4-pole	—		—		—		—		1492-CJJ5-3		50	
Screw Center Jumper — 3-pole	—		—		—		—		1492-CJJ5-2		50	
Screw Center Jumper — 2-pole	—		—		—		—		1492-SJ5A-24		50	
Insulated Side Jumper — 24-Pole	—		—		—		—		1492-SJ5A-10		50	
Insulated Side Jumper — 10-Pole	—		—		—		—		—		—	
End Anchors and Retainers:	—		—		—		—		1492-ERL35		20	
Screwless End Retainer	—		—		—		—		1492-EAJ35		100	
DIN Rail — Normal Duty	—		—		—		—		1492-EAHJ35		50	
DIN Rail — Heavy Duty	1492-EAHJ35		50		1492-EAHJ35		50		1492-EAHJ35		50	
Marking Systems:	1492-M7X12 (108/card)		5		1492-MR8X12 (84/card)		5		1492-M5X8 (200/card)		5	
Snap-in marker cards	1492-M8X5 (160/card)		5		1492-M7X12 (108/card)		5		1492-M5X5 (144/card)		5	
Snap-in marker cards	—		—		—		—		—		—	

