

6	7 8
SPE	ECIFICATIONS
CERTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED
PLING NUT MATERIAL	EPOXY-COATED ZINC
TOR OVERMOLD MATERIAL	OIL RESISTANT PUR
CONTACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL
CONTACT MATERIAL	BRASS OR COPPER ALLOY
CABLE TYPE	PVC, 22AWG, 300V
BLE JACKET COLOR	YELLOW
BEND RADIUS	IO X DIAMETER
R OF CONDUCTORS [AWG]	3 x 2 2 A W G
SHIELDING	UNSHIELDED
CABLE RATING	UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B
	I/II 80C 300V FTI, UV OIL AND WATER RESISTANT
GRESS PROTECTION MPERATURE RATING	-20° +105°C (-4° +221°F)
	$\frac{47}{[1.85]}$
FOR LATEST	47 1.853 47 1.853 47 1.853 47 CINTRE FOR REFERENCE ONLY AND UPDATE PLEASE REFER http://www.ab.com/catalogs/ Rockwell utomation
FOR LATEST	
FOR LATEST	47 E1.85] 47 E1.85] 47 E1.85] 47 E1.85] ENFORMATION SHOWN ARE FOR REFERENCE ONLY AND UPDATE PLEASE REFER http://www.ab.com/catalogs/ Rockwell utomation Proprietary Information. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION. CONFIDENTIAL AND PROPRIETARY