

|                       | 7 8   |
|-----------------------|---|
| SP [                  | ECIFICATIONS  |
| CERTIFICATIONS        | UL RECOGNIZED AND CSA CERTIFIED   |
| PLING NUT MATERIAL    | EPOXY-COATED ZINC   |
| TOR OVERMOLD MATERIAL | OIL RESISTANT PUR   |
| CONTACT PLATING       | GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL  |
| CONTACT MATERIAL      | BRASS OR COPPER ALLOY   |
| CABLE TYPE            | PVC, 22AWG, 300V  |
| BLE JACKET COLOR      | YELLOW  |
| BEND RADIUS           | IO X DIAMETER   |
| OF CONDUCTORS [AWG]   | 3 x 2 2 A W G   |
| SHIELDING             | UNSHIELDED  |
| CABLE RATING          | UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B   |
|                       | I/II 80C 300V FTI, UV OIL AND WATER RESISTANT   |
| GRESS PROTECTION      | -20° +105°C (-4° +221°F)  |
| MPERATURE RATING      |   |
|                       |   |
|                       | $\frac{47}{[1.85]}$   |
|                       |   |
|                       |   |
| FOR LATEST            | & INFORMATION SHOWN ARE FOR REFERENCE ONLY AND  |
| FOR LATEST            | (.55] (   |
| FOR LATEST            | 47 1.853 47 1.853 47 Clission Control of the second of th |