

	0		/	8		
	SP	ECIFIC	ATIONS			
TIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED				
IG NUT MATE	RIAL	EPOXY-COATED ZINC				
OVERMOLD M	1A T E R I A L	OIL RESISTANT PUR				
ACT PLATIN	IG	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL				
ACT MATERIAL		BRASS OR COPPER ALLOY				
ABLE TYPE		PVC, 22AWG, 300V				
JACKET COLOR		GRAY				
ND RADIUS		IO X DIAMETER				
CONDUCTORS [AWG]		2x22 AWG				
HIELDING		UNSHIELDED				
BLE RATING		UL PLTC AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT				
S PROTECTION		IP67 & IP69K				
ATURE RATI	NG		-20°+105°C (-4°.	. +221°F)		

FOR LAIESI	UPDAIE PLEASE	KEFEK	http://www.ab.com/catalogs/ confidential and proprietary information.
			ARE FOR REFERENCE ONLY AND

	Rockwell tomation	THIS DOC INFORM NOT BE	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.			
		Sheet   Of   Size   Ver				
	D-F2GCDM-*	C	889D-F2GCDM-*			
Drawn by: LNT	Date: 12/4/2013					