

	7 8
S	PECIFICATIONS
CERTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED
PLING NUT MATERIAL	EPOXY-COATED ZINC
TOR OVERMOLD MATERIAL	OIL RESISTANT PUR
CONTACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL
CONTACT MATERIAL	BRASS OR COPPER ALLOY
CABLE TYPE	PVC, I8AWG, 300V
BLE JACKET COLOR	YELLOW
BEND RADIUS	IO X DIAMETER
R OF CONDUCTORS [AWG]	3 x I 8 AWG
SHIELDING	UNSHIELDED
CABLE RATING	UL AWM STYLE 20866 VW-I 80C 300V, CSA AWM A/B I/II 80C 300V FTI, UV OIL AND WATER RESISTANT
GRESS PROTECTION	NEMA 6P, I200 PSI (8270 kPa) WASHDOWN, IP69K
MPERATURE RATING	-20° +80°C (-4° +176°F)
	47 [1.85]
FOR LATE	Image: State of the state
FOR LATE	Image: Strain
FOR LATE	A7 I.55] A7 I.85] I.85] I.85] DNS & INFORMATION SHOWN ARE FOR REFERENCE ONLY AND EST UPDATE PLEASE REFER http://www.ab.com/catalogs/ Rockweell Automation Information Virtuation Sheet I Of I 889D-F3UEDM-*