

;	6	7	8
		•	

0		/	0		
SPECIFICATIONS					
CERTIFICATIONS		RoHS, cULus, CSA, cURus???			
OUPLING NUT MATERIAL		EPOXY-COATED ZINC			
CTOR OVERMOLD MATERIAL		OIL RESISTANT PUR			
CONTACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
CONTACT MATERIAL		BRASS OR COPPER ALLOY			
CABLE TYPE		PVC, I8AWG, 300V			
CABLE JACKET COLOR		YELLOW			
BEND RADIUS		IO X DIAMETER			
ER OF CONDUCTORS [AWG]		4 x I 8 AWG			
SHIELDING		UNSHIELDED			
CABLE RATING		UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT			
NGRESS PROTECTION		A 6P, I200 PSI (8270 I	(Pa) WASHDOWN, IP69K		
EMPERATURE RATING		-20°+105°C (-4	° +22 °F)		

DIMENSIONS & INFORMATION SHOWN ARE	
FOR LATEST UPDATE PLEASE REFER http	p://www.ab.com/catalogs/
Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.
	Sheet Of
	Size Ver