

;	6	7	8	

	0		/	0	
	SPEC		ICATIONS		
CERTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED			
OUPLING NUT MATERIAL		EPOXY-COATED ZINC			
CTOR OVERMOLD MATERIAL		OIL RESISTANT PUR			
CONTACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
CONTACT MATERIAL		BRASS OR COPPER ALLOY			
CABLE TYPE		PVC, 22AWG, 300V			
CABLE JACKET COLOR		YELLOW			
BEND RADIUS		IO X DIAMETER			
ER OF CONDU	JCTORS [AWG]		4 x 2 2 A	NG	
SHIELD	ING		FOIL		
CABLE RATING			WM STYLE 2661 VW-1 10 80C 300V FT1, UV OIL	,	
NGRESS PROTECTION			NEMA 6P, I200 PSI (8270 kPa) WASHDOWN, IP69K		
EMPERATURE RATING		$-20^{\circ} \dots + 105^{\circ}C (-4^{\circ} \dots + 221^{\circ}F)$			

DIMENSIONS & INFORMATION SHOWN FOR LATEST UPDATE PLEASE REFER		
Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL	

		A				
		Sheet   Of				
	889D-F4FCDM-*	Size		Ver		
		C	889D-F4FCDM-*			
Drawn by: LNT	Date:   / 4/20 3			0.0		