

, SPE(CIFICATIONS
CERTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED
UPLING NUT MATERIAL	EPOXY-COATED ZINC
CTOR OVERMOLD MATERIAL	OIL RESISTANT PUR
CONTACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL
CONTACT MATERIAL	BRASS OR COPPER ALLOY
CABLE TYPE	PVC, 22AWG, 300V
CABLE JACKET COLOR	YELLOW
BEND RADIUS	IO X DIAMETER
R OF CONDUCTORS [AWG]	5x22 AWG
SHIELDING	UNSHIELDED
CABLE RATING	UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT
NGRESS PROTECTION	NEMA 6P, I200 PSI (8270 kPa) WASHDOWN, IP69K
EMPERATURE RATING	$-20^{\circ} \dots + 05^{\circ}C (-4^{\circ} \dots + 22 ^{\circ}F)$
	——————————————————————————————————————

				ARE FOR REFERENCE ONLY AND
	FOR LATEST	UPDATE PLEASE	REFER	http://www.ab.com/catalogs/
Γ				

Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.			
	Sheet Of			
889D-F5ACDM-*	Size Ver			
Drawn by: LNT Date: 10/08/2013	— C 889D-F5ACDM-* 0.0			