

6	7 8
S P E	ECIFICATIONS
CERTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED
PLING NUT MATERIAL	EPOXY-COATED ZINC
TOR OVERMOLD MATERIAL	OIL RESISTANT PUR
CONTACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL
CONTACT MATERIAL	BRASS OR COPPER ALLOY
CABLE TYPE	PVC, 22AWG, 300V
ABLE JACKET COLOR	YELLOW
BEND RADIUS	IO X DIAMETER
R OF CONDUCTORS [AWG]	5 x 2 2 A W G
SHIELDING	BRAIDED
CABLE RATING	UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FT1, UV OIL AND WATER RESISTANT
GRESS PROTECTION	NEMA 6P, I200 PSI (8270 kPa) WASHDOWN, IP69K
MPERATURE RATING	$-20^{\circ}+105^{\circ}C(-4^{\circ}+221^{\circ}F)$
	MI2x1 Ø14 [.55]
FOR LATEST	A7     L1.851      SINFORMATION SHOWN ARE FOR REFERENCE ONLY AND UPDATE PLEASE REFER http://www.db.com/cdtalogs/      Rockweii utomation
FOR LATEST	47 E11.851 47 E1.851 47 E1.851 47 E1.851 47 E1.851 47 E1.851 Ended the formation of the second of the