

	6		/	8
	SP	ECIFIC	ATIONS	
TIFICATION	S		UL RECOGNIZED AND CS	A CERTIFIED
G NUT MATERIAL		EPOXY-COATED ZINC		
OVERMOLD MATERIAL		OIL RESISTANT PUR		
ACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL		
ACT MATERIAL		BRASS OR COPPER ALLOY		
ABLE TYPE			PVC, 22AWG, 3	300V
JACKET COLOR		GRAY		
ND RADIUS		IO X DIAMETER		
CONDUCTORS [AWG]		5x22 AWG		
GHIELDING		UNSHIELDED		
BLE RATING			AWM STYLE 2661 VW-1 IC 80C 300V FTI, UV OIL	
S PROTECTI	ON		IP67 & IP69) K
ATURE RATI	NG		-20° + $ 05^{\circ}$ C (-4° .	+22 °F)

FOR LATEST UPDATE PLEASE REFER h				
Rockwell Automation	THIS INFC NOT B	CONFIDENTIAL AND PROPRIETARY INFORMATION. DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIE ORMATION OF ROCKWELL AUTOMATION, INC. AND M SE USED, COPIED OR DISCLOSED TO OTHERS, EXC THE AUTHORIZED WRITTEN PERMISSION OF ROCKW AUTOMATION, INC.	MAY Cept	
		Sheet I Of I		
889D-F5GCDM-*	Size		Ver	
	— c	889D-F5GCDM-*	$\cap \cap$	
Drawn by: LNT Date: 12/4/2013			v . v	