

	6 7 8			
S	PECIFICATIONS			
RTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED			
NG NUT MATERIAL	EPOXY-COATED ZINC			
OVERMOLD MATERIAL	OIL RESISTANT TPE			
TACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
FACT MATERIAL	BRASS OR COPPER ALLOY			
CABLE TYPE	PVC, I8AWG, 300V			
JACKET COLOR	YELLOW			
END RADIUS	IO X DIAMETER			
CONDUCTORS [AWG]	2 x I 8 AWG			
SHIELDING	UNSHIELDED			
ABLE RATING	UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/1 80C 300V FTI, UV OIL AND WATER RESISTANT			
SS PROTECTION	NEMA 4, 6P, 12, 13; 1P67; 1200 PSI WASHDOWN, 1P69K			
RATURE RATING	$-20^{\circ}+105^{\circ}C(-4^{\circ}+221^{\circ}F)$			

FOR LATEST UPDATE PLEASE						
Rockwell Automation		THIS D INFOF NOT BE	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.			
889N-F2AENV-* Drawn by: LNT Date: 03/10/2014			Sheet Of			
		Size		Ver		
		— C	889N-F2AENV-*	0.0		