

	6		7	8	
	SPI	EC F (CATIONS		
RTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED			
NG NUT MATERIAL		EPOXY-COATED ZINC			
OVERMOLD MATERIAL		OIL RESISTANT TPE			
TACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
TACT MATERIAL		BRASS OR COPPER ALLOY			
CABLE TYPE		PVC, I6AWG, 600V			
E JACKET COLOR		YELLOW			
END RADIUS		IO X DIAMETER			
F CONDUCTORS [AWG]		2x16 AWG			
SHIELDING		UNSHIELDED			
ABLE RATING)		N VW-I 105C 600V, CSA AND WATER RESISTANT	ST 105C 600V FT2,	
SS PROTECT	ION	NEMA 4,	6P, I2, I3; IP67; I20) PSI WASHDOWN, IP69K	
RATURE RATING		$-20^{\circ} \dots + 105^{\circ}C (-4^{\circ} \dots + 221^{\circ}F)$			

FOR LATEST UPDATE PLEASE REFER htt	-		╞
Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
	Sheet Of		
889N-F2AFNU-*	Size	Ver	
	С	889N-F2AFNU-* 0.	0
Drawn by: LNT Date: 03/10/2014		I	
		1	