

	6		7	8		
	SP	ECIFIC	CATIONS			
RTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED				
NG NUT MATERIAL		EPOXY-COATED ZINC				
OVERMOLD MATERIAL		OIL RESISTANT TPE				
TACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL				
TACT MATERIAL		BRASS OR COPPER ALLOY				
CABLE TYPE		PVC, I6AWG, 600V				
E JACKET COLOR		YELLOW				
END RADIUS		IO X DIAMETER				
F CONDUCTORS [AWG]		2x16 AWG				
SHIELDING		UNSHIELDED				
ABLE RATING		UL STOOW VW-I 105C 600V, CSA ST 105C 600V FT2, UV OIL AND WATER RESISTANT				
SS PROTECTION		NEMA 4, 6P, 12, 13; IP67; I200 PSI WASHDOWN, IP69K				
RATURE RATING		-20° +105°C (-4° +221°F)				
		1				

FOR LATEST UPDATE PLEASE REFER htt	-		
Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
	Sheet Of		
889N-F2AFNV-*	Size	V	er
		889N-F2AFNV-*	\cap
Drawn by: LNT Date: 03/10/2014			0.0
Drawn by: LNT Date: 03/10/2014	С	009N-FZAFNV-*	. 0