

	6		7	8	
	SPE	$EC \mid F \mid ($	CATIONS		
RTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED			
NG NUT MATERIAL		EPOXY-COATED ZINC			
OVERMOLD MATERIAL		OIL RESISTANT TPE			
TACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
TACT MATERIAL		BRASS OR COPPER ALLOY			
CABLE TYPE		PVC, I6AWG, 600V			
E JACKET COLOR		YELLOW			
END RADIUS		IO X DIAMETER			
F CONDUCTORS [AWG]		3x16 AWG			
SHIELDING		UNSHIELDED			
ABLE RATING		UL STOOW VW-I 105C 600V, CSA ST 105C 600V FT2, UV OIL AND WATER RESISTANT			
SS PROTECTION		NEMA 4, 6P, I2, I3; IP67; I200 PSI WASHDOWN, IP69K			
RATURE RATING		$-20^{\circ} \dots + 105^{\circ}C (-4^{\circ} \dots + 221^{\circ}F)$			

				AUTOMATION, INC.		
				Sheet I Of I		
		889N-F3AFNV-*	Size		Ver	
			— c	889N-F3AFNV-*	0.0	
-	Drawn by: LNT	Date: 03/10/2014			••••	