

	7	8	
SPECIFICATIONS			
UL RECOGNIZED AND CSA CERTIFIED			
EPOXY-COATED ZINC			
OIL RESISTANT TPE			
GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
BRASS OR COPPER ALLOY			
TPE, I6AWG, 600V			
YELLOW			
IO X DIAMETER			
3x16 AWG			
UNSHIELDED			
UL SEOOW VW-I 105C -50C 600V WATER RESISTANT, CSA STOO FT-I 600V			
NEMA 4, 6	SP, 12, 13; 1P67; 120	0 PSI WASHDOWN, IP69K	
	-50° +105°C (-58°	+221°F)	
	GOLI	ECIFICATIONS UL RECOGNIZED AND CS EPOXY-COATED OIL RESISTANT GOLD OR GOLD FLASH OVER BRASS OR COPPER TPE, I6AWG, YELLOW IO X DIAMET 3x16 AWG UNSHIELDE UL SEOOW VW-1 105C -50C 600V	

FOR LATEST UPDATE PLEASE REFER htt			
Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
	Sheet   Of		
889N-F3HFNU-*	Size Ver		
Drawn by: LNT Date: 03/10/2014	<b>C</b> 889N-F3HFNU-* 0.0		