

6	i 7 8
S F	PECIFICATIONS
RTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED
NG NUT MATERIAL	EPOXY-COATED ZINC
OVERMOLD MATERIAL	OIL RESISTANT TPE
TACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL
ACT MATERIAL	BRASS OR COPPER ALLOY
CABLE TYPE	PVC, I8AWG, 300V
E JACKET COLOR	GRAY
IND RADIUS	IO X DIAMETER
CONDUCTORS [AWG]	4 x I 8 AWG
SHIELDING	UNSHIELDED
ABLE RATING	UL PLTC AWM STYLE 266IVW-I 105C 300V, CSA AWM A/B I/II 80C 300V FTI, UV OIL AND WATER RESISTANT
SS PROTECTION	NEMA 4, 6P, I2, I3; IP67; I200 PSI WASHDOWN, IP69K
RATURE RATING	-20° + 05°C (-4° +221°F)

DIMENSIONS & INFORMATION SHOWN ARE FOR LATEST UPDATE PLEASE REFER http		
Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETAR INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.	т
	Sheet Of	
889N-F4GENU-*	Size Ve) r