

	6	7 8			
	SP	PECIFICATIONS			
RTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED			
NG NUT MATERIAL		EPOXY-COATED ZINC			
OVERMOLD MATERIAL		OIL RESISTANT TPE			
TACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
TACT MATERIAL		BRASS OR COPPER ALLOY			
CABLE TYPE		PVC, I8AWG, 300V			
E JACKET COLOR		YELLOW			
END RADIUS		IO X DIAMETER			
F CONDUCTORS [AWG]		5x18 AWG			
SHIELDING		UNSHIELDED			
ABLE RATING		UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT			
SS PROTECTION		NEMA 4, 6P, 12, 13; IP67; I200 PSI WASHDOWN, IP69K			
RATURE RATING		-20° +105°C (-4° +221°F)			

DIMENSIONS & INFORMATION SHOWN ARE FOR REFERENCE ONLY AND FOR LATEST UPDATE PLEASE REFER http://www.ab.com/catalogs/

Rockwell Automation			CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
		Sheet Of			
88	9 N - F 5 A E N U - *	Size		Ver	
		— c	889N-F5AENU-*		
Drawn by: LNT	Date: 03/10/2014	U		••••	