

	6		7	8		
	SP	ECIFICAT	TIONS			
RTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED				
NG NUT MATERIAL		EPOXY-COATED ZINC				
OVERMOLD MATERIAL		OIL RESISTANT TPE				
TACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL				
TACT MATERIAL		BRASS OR COPPER ALLOY				
CABLE TYPE		PVC, I8AWG, 300V				
E JACKET COLOR		GRAY				
END RADIUS		IO X DIAMETER				
F CONDUCTORS [AWG]		5x18 AWG				
SHIELDING		UNSHIELDED				
ABLE RATING		UL PLTC AWM STYLE 266IVW-I 105C 300V, CSA AWM A/B I/II 80C 300V FTI, UV OIL AND WATER RESISTANT				
SS PROTECTION		NEMA 4, 6P, 12, 13; IP67; I200 PSI WASHDOWN, IP69K				
RATURE RATING		- [20° + 105°C	(-4°+221°F)		

	tomation	INFORM NOT BE	ATION OF ROCKWELL AUTOMATION, INC. A USED, COPIED OR DISCLOSED TO OTHERS, E AUTHORIZED WRITTEN PERMISSION OF F AUTOMATION, INC.	ND MAY EXCEPT		
			Sheet Of			
883) N - F 5 G E N U - *	Size		Ver		
		— c	889N-F5GENU-*	0 0		
Drawn by: LNT	Date: 03/10/2014			○. ○		