

	6	7	8					
SPECIFICATIONS								
RTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED						
NG NUT MATERIAL		EPOXY-COATED ZINC						
OVERMOLD MATERIAL		OIL RESISTANT TPE						
TACT PLATING	GOL	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL						
TACT MATERIAL		BRASS OR COPPER ALLOY						
CABLE TYPE		PVC, 18AWG, 300V						
E JACKET COLOR		YELLOW						
END RADIUS		IO X DIAMETER						
F CONDUCTORS [AWG]		3x18 AWG						
SHIELDING		UNSHIELDED						
ABLE RATING		UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT						
SS PROTECTION	NEMA 4,	6P, I2, I3; IP67; I20	0 PSI WASHDOWN, IP69K					
RATURE RATING		$-20^{\circ} \dots + 105^{\circ}C (-4^{\circ} \dots + 221^{\circ}F)$						

	JPDATE PLEASE REFER			/www.ab.com/catal		
Rockwell Automation				CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
		Sheet I Of I				
889N - R 3AENV - *			Size		Ver	
Drawn by: LNT	Date: 03/10/2014		С	889N - R3AENV - *	0.0	