

5	6	7		8	
	SPE	ECIFICATIONS		·	
RTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED			
NG NUT MATERIAL		DC MICRO: BLACK EPOXY-COATED ZINC, PICO: NICKEL-PLATED BRASS			
R OVERMOLD MATERIAL		DC MICRO: MOLDED OIL-RESISTANT PUR, PICO: MOLDED OIL-RESISTANT TPE			
ITACT PLATING		GOLD OVER NICKEL-PLATED BRASS			
TACT MATERIAL		BRASS OR COPPER ALLOY			
CABLE TYPE		PVC, 24AWG, 300V			
E JACKET COLOR		YELLOW			
end radius		IO X DIAMETER			
F CONDUCTO	rs [awg]	4X24 AWG (MICRO MA	LE), 4X24	AWG (PICO FEMALE)	
SHIELDING		UNSHIELDED			
ABLE RATING	Ĵ	UL CM AWM STYLE 2 AWM A/B I	661 VW-1 /11 105°C	105°C 300V, CSA 300V FTI	
SS PROTECT	ION		IP67		
RATURE RATING		$-20^{\circ}+105^{\circ}C(-4^{\circ}+221^{\circ}F)$			

Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.			
		Sheet Of Size Ver		
889P-F4ABDM-* Drawn by: LNT Date: 05-14-2015	- C	889P-F4ABDM-*	0.0	