

6	7	8	
SPE(CIFICATIONS		
CERTIFICATIONS	UL RECOGNIZED AND	CSA CERTIFIED	
UPLING NUT MATERIAL	ΕΡΟΧΥ-COATE	D ZINC	
CTOR OVERMOLD MATERIAL	OIL RESISTANT PUR		
CONTACT PLATING	GOLD OR GOLD FLASH OVE	R PALLADIUM-NICKEL	
CONTACT MATERIAL	BRASS OR COPP	ER ALLOY	
CABLE TYPE	PVC, 22AWG	, 300V	
CABLE JACKET COLOR	YELLO	N	
BEND RADIUS	IO X DIAM	E T E R	
R OF CONDUCTORS [AWG]	3 x 2 2 A	NG	
SHIELDING	BRAIDE	D	
CABLE RATING	UL AWM STYLE 2661 VW-1 10 1/11 80C 300V FT1, UV OIL		
NGRESS PROTECTION	IP67, IP	69K	
EMPERATURE RATING	-20°+105°C (-4	° +221°F)	
		—M 2 x	

DIMENSIONS & INFORMATION SHOWN ARE			
FOR LATEST UPDATE PLEASE REFER htt	p://www.ab.com/catalogs/		
Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
	Sheet Of		
889R-F3ECRE-*	Size Ver		
Drawn by: LNT Date: 04/28/2014	C 889R-F3ECRE-* 0.0		