

SPECIFICATIONS CERTIFICATIONS UL RECOON ZED AND CSA CERTIFIED UDLINC NUT MATERIAL EPOXY-COATED ZINC CONTACT PLATING GOLD GR COLD FLASH OVER PALLADIUM-NICKEL CONTACT NATERIAL BRASS OR COPPER ALLOY CABLE TYPE PVC. TRANG, 390V CABLE JACKET COLOR YELLOW BEND RADIUS 19 X DIAMETER EN OF CONDUCTORS LAWSI NUS STYLE 2661 VW-1 TOSC 300V, CSA AWM AZA CABLE RATING UL AWK STYLE 2661 VW-1 TOSC 300V, CSA AWM AZA CABLE RATING UL AWK STYLE 2661 VW-1 TOSC 300V, CSA AWM AZA CABLE RATING UL AWK STYLE 2661 VW-1 TOSC 300V, CSA AWM AZA CABLE RATING -20° +105°C (-4° +221°F)	6	7 8
UPLING NUT MATERIAL EPOXY-COATED ZINC CTOR OVERVOLD WATERIAL OIL RESISTANT PUR CONTACT PLATING GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL CONTACT MATERIAL BRASS OR COPPER ALLOY CABLE TYPE PVC, IBAWG, 300V CABLE JACKET COLOR YELLOW BEND RADIUS 10 X DIAMETER TR OF CONDUCTORS TAWG1 4x18 AWS SHIELDING UNAMESTYLE 2661 VA-11 OSC 300V, CSA AWM A/3 I/TI 80C 300V FH, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP694 EVPERATURE RATING 20° +IOS°C (-4° +221°C)	SPE	CIFICATIONS
CTOR OVERVOLD WATERIAL OIL RESISTANT PUR CONTACT PLATINS GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL CONTACT WATERIAL BRASS OR COPPER ALLOY CABLE TYPE PVC, I8AWG, 300V CABLE JACKET COLOR YELLOW BEND RADIUS IO X DIAMETER ER OF CONDUCTORS [AWG] 4x18 AWG SHIELDING UNSHIELDED CABLE RATING ULL AWM STYLE 2661 VW-1 TOSC 300V, CSA AWM A/B T/TI 80C 300V FTI, UV OIL AND WATER RESISTANT NGRESS PROFECTION IP67, IP69K IMPERATURE RATING 20° (165°C (4° (221°T))	CERTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED
CONTACT PLATING COLD OR GOLD FLASH OVER PALLADIUM NICKFL CONTACT WATERIAL BRASS OR COPPER ALLOY CABLE TYPE PVC, ISAWG, 300V CABLE TYPE PVC, ISAWG, 300V CABLE JACKEL COLOR YELLOW DEND RADIUS IO X DIAMETER ER OF CONDUCTORS LAWGI 4x18 AWG SHIELDING UL ANM STYLE 2661 VW-1 IOSC 300V, CSA AWM A/B CABLE RATING UL ANM STYLE 2661 VW-1 IOSC 300V, CSA AWM A/B CABLE RATING UL ANM STYLE 2661 VW-1 IOSC 300V, CSA AWM A/B RESS PROTECTION IP67, IP69K FMPERATURE RATING 20° +IOS°C (-4° +221°E)	UPLING NUT MATERIAL	EPOXY-COATED ZINC
CONTACT MATERIAL BRASS OR COPPER ALLOY CABLE TYPE PVC, T8AWG, 300V CABLE JACKET COLOR YELLOW BEND RADIUS TO X DIAMETER TR OF CONDUCTORS TANGI 4x18 AWG SHIELDING UL AWW STYLE 2661 VW-1 TO5C 300V, CSA AWW A/B T/TT 80C 300V FTT, UV OIL AND WATER RESISTANT NGRESS PROTECTION TP67, TP69K FWPFRATURE RATING -20° +105°C (-4° +221°F) -VT2x1 -	CTOR OVERMOLD MATERIAL	OIL RESISTANT PUR
CABLE TYPE PVC. 18AWG. 300V CABLE JACKET COLOR YELLOW BEND RADIUS 10 X DIAMETER ER OF CONDUCTORS LAWGI 4x18 AWG SHIELDING UNSHIELDED CABLE RATING UL AWM STYLE 2661 VW-L 105C 300V, CSA AWM A/5 I/TI 80C 300V FTI, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP69K EMPERATURE RATING 20° +105°C (-4° +221°F)	CONTACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL
CABLE JACKET COLOR YELLOW BEND RADIUS IO X DIAMETER IR OF CONDUCTORS LAWCI 4x18 AWC SHIELDING UNSHIELDED CABLE RATING UL AWM STYLE 2661 VW-TI TOSC 300V, CSA AWM A/B I/TI 80C 300V FTI, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP69K EMPERATURE RATING -20° +105°C (-4° +221°F) MI2x1 MI2x1 MI2x1 MI2x1 MI2x1	CONTACT MATERIAL	BRASS OR COPPER ALLOY
BEND RADIUS IO X DIAMETER ER OF CONDUCTORS [AWG] 4x18 AWG SHIELDING UNSHIELDED CABLE RATING UL AWM STYLE 2661 VW I LOSC 300Y, CSA AWM A/B I/II 80C 300V FTI, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP69K EMPERATURE RATING -20° +IOS°C (-4° +221°F)	CABLE TYPE	PVC, I8AWG, 300V
R OF CONDUCTORS LAWGI SHIELDING CABLE RATING UL AWM STYLE 2661 VW-1 LOSC 300V, CSA AWM A/B L/11 80C 300V FTL, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP69K EMPERATURE RATING -20° +105°C (-4° +221°L) V12x1 V12x1 V12x1 V12x1 V12x1 V12x1	CABLE JACKET COLOR	YELLOW
SHIELDING UNSHIELDED CA3LE RATING UL AWM STYLE 2661 VW-I 105C 300V, CSA AWM A/B I/II 80C 300V FTI, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP69K EMPERATURE RATING -20° +105°C (-4° +221°F)	BEND RADIUS	IO X DIAMETER
CABLE RATING UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B I/II 80C 300V FTI, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP69K EMPERATURE RATING -20° +105°C (-4° +221°F) MI2x1 MI2x1 MI2x1 MI2x1 MI2x1 AT	ER OF CONDUCTORS [AWG]	4 x I 8 AWG
CABLE HAITING 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT NGRESS PROTECTION IP67, IP69K EMPERATURE RATING -20° +105°C (-4° +221°F)	SHIELDING	UNSHIELDED
EMPERATURE RATING -20° +105°C (-4° +221°F) Image: Milling of the second secon	CABLE RATING	
	NGRESS PROTECTION	IP67, IP69K
	EMPERATURE RATING	-20° + 05°C (-4° +22 °F)

DIMENSIONS & INFORMATION SHOWN ARE FOR REFERENCE ONLY AND FOR LATEST UPDATE PLEASE REFER http://www.ab.com/catalogs/

Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
	Sheet I Of I		
889R - F 4 A E R M - *	Size Ver		
	∼ 889R-F4AERM-* ∩ ∩		
Drawn by: LNT Date: 04/28/2014			