

ςΡ	ECIFICATIONS			
CERTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED			
JPLING NUT MATERIAL	EPOXY-COATED ZINC			
TOR OVERMOLD MATERIAL	OIL RESISTANT PUR			
CONTACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL			
CONTACT MATERIAL	BRASS OR COPPER ALLOY			
CABLE TYPE	PVC, I8AWG, 300V			
ABLE JACKET COLOR	YELLOW			
BEND RADIUS	IO X DIAMETER			
R OF CONDUCTORS [AWG]	5x18 AWG			
SHIELDING	UNSHIELDED			
CABLE RATING	UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT			
IGRESS PROTECTION	IP67, IP69K			
MPERATURE RATING	$-20^{\circ}+105^{\circ}C(-4^{\circ}+221^{\circ}F)$			
	MI2x1 Ø14 [.55]			

DIMENSIONS	& INFORMATION	SHOWN	ARE FOR REFERENCE ONLY AND
FOR LATEST	UPDATE PLEASE	REFER	http://www.ab.com/catalogs/

Rockwell Automation	THIS D INFOI NOT BI	CONFIDENTIAL AND PROPRIETARY INFORMATION. DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIE RMATION OF ROCKWELL AUTOMATION, INC. AND I E USED, COPIED OR DISCLOSED TO OTHERS, EX THE AUTHORIZED WRITTEN PERMISSION OF ROCK' AUTOMATION, INC.	ETARY MAY CEPT
	Sheet   Of		
889R-F5AERM-*	S i z e	889R-F5AERM-*	Ver
Drawn by: LNT Date: 04/28/2014			0.0