

·

6	7	8		
SP	ECIFICATIONS			
CERTIFICATIONS	UL RECOGNIZED	AND CSA CERTIFIED		
UPLING NUT MATERIAL	EPOXY-C	EPOXY-COATED ZINC		
CTOR OVERMOLD MATERIAL	OIL RES	ISTANT PVC		
CONTACT PLATING	GOLD OR GOLD FLASH	OVER PALLADIUM-NICKEL		
CONTACT MATERIAL	BRASS OR	COPPER ALLOY		
CABLE TYPE	PUR, I8	BAWG, 300V		
CABLE JACKET COLOR	YELLOW			
BEND RADIUS	IO X DIAMETER			
R OF CONDUCTORS [AWG]	5 x	I8 AWG		
SHIELDING	UNSE	HIELDED		
CABLE RATING	UL AWM, UV, OIL AND W	ATER RESISTANT, I8 AWG		
NGRESS PROTECTION	IP67	, IP69K		
EMPERATURE RATING	- 20° + 80°C	(-4°+ 05°F)		
	S & INFORMATION SHOWN ARE T UPDATE PLEASE REFER h++			
	Rockwell	CONFIDENTIAL AND PROPRIETARY INFORMATION.		
	utomation	INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.		
		Sheet Of Size Ver		
	889R-F5UERM-*	889R-E5UERM-*		

Date: 04/28/2014

Drawn by: LNT

889R-F5UERM-*

С