

6		7		8		
SP	ECIFICAT	IONS				
CERTIFICATIONS	UL	RECOGNIZED	AND CSA CE	RTIFIED		
IPLING NUT MATERIAL		EPOXY-COATED ZINC				
TOR OVERMOLD MATERIAL		OIL RESISTANT PUR				
CONTACT PLATING	GOLD OI	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL				
CONTACT MATERIAL		BRASS OR COPPER ALLOY				
CABLE TYPE		PVC, 22AWG, 300V				
ABLE JACKET COLOR		YELLOW				
BEND RADIUS		IO X DIAMETER				
R OF CONDUCTORS [AWG]		6 x 2 2 A W G				
SHIELDING		BRAIDED				
CABLE RATING		UL AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 80C 300V FTI, UV OIL AND WATER RESISTANT				
IGRESS PROTECTION		IP67, IP69K				
MPERATURE RATING	- 2	$20^{\circ} \dots + 105^{\circ}$	C (-4°+	221°F)		
				Ø 4 [.55]		
	-	47 - [I.85]				
DIMENSIONS	S & INFORMATI	on shown ar	F FOR RFFR	ENCE ONLY AND		
				.com/catalogs/		
	Rockwe utomatie		THIS DOCUMENT CONTAI INFORMATION OF ROCK NOT BE USED, COPIED WITH THE AUTHORIZED	ID PROPRIETARY INFORMATION. NS CONFIDENTIAL AND PROPRIETARY WELL AUTOMATION, INC. AND MAY OR DISCLOSED TO OTHERS, EXCEPT WRITTEN PERMISSION OF ROCKWELL TOMATION, INC.		
	889R-F6ECRM-*		Size Size	eet Of Ver		
			- c 889R	-F6ECRM-* 0.0		
Drawn by: LNT	Date: 04	4/28/20 4				
