

	6			/	8	
	S P E	$EC \mid F \mid ($	CATIONS)		
ERTIFICATIONS		UL RECOGNIZED AND CSA CERTIFIED				
ING NUT MATERIAL		EPOXY-COATED ZINC				
R OVERMOLD MATERIAL		OIL RESISTANT PVC				
NTACT PLATING		GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL				
ITACT MATER	RIAL	BRASS OR COPPER ALLOY				
CABLE TYPE		PVC, 22AWG, 300V				
E JACKET COLOR		GREY				
BEND RADIUS		IO X DIAMETER				
OF CONDUCTORS [AWG]		6x22 AWG				
SHIELDING		BRAIDED				
CABLE RATING		UL PLTC AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B I/II 80C 300V FTI, UV OIL AND WATER RESISTANT				
ESS PROTECTION		IP67 & IP69K				
ERATURE RATING		-20° +105°C (-4° +221°F)				

Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.			
	Sheet Of			
889R-F6KCRM-*	Size	Ver		
		889R-F6KCRM-* 🕠 🕥		
Drawn by: LNT Date: 04/28/2014				