

6	6	7	8		
SP	PEC F C	ATIONS			
TIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED				
G NUT MATERIAL	EPOXY-COATED ZINC				
OVERMOLD MATERIAL	OIL RESISTANT PVC				
ACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL				
ACT MATERIAL	BRASS OR COPPER ALLOY				
ABLE TYPE	PVC, I8AWG, 300V				
JACKET COLOR	YELLOW				
ND RADIUS	IO X DIAMETER				
CONDUCTORS [AWG]	3 x 8 A W G (A	AC MICRO FEMALE) & 4;	(I8AWG(DC MICRO MALE)		
HIELDING	UNSHIELDED				
BLE RATING	UNSHIELDED,OIL,WATER, AND UV RESISTANT, AWM, 18 AWG				
S PROTECTION		I P 6 7			
ATURE RATING		$-20^{\circ} \dots + 105^{\circ}C (-4^{\circ} \dots + 221^{\circ}F)$			

Rockwell Automation	CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.
889R-R3AEDE-*	Sheet Of Size Ver
Drawn by: LNT Date: 04/28/	c 889R-R3AEDE-* 0.0