

6	7	8	
SPE	CIFICATIONS		
CERTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED		
UPLING NUT MATERIAL	EPOXY-COATED ZINC		
CTOR OVERMOLD MATERIAL	OIL RESISTANT PVC		
CONTACT PLATING	GOLD OR GOLD FLASH OVER PALLADIUM-NICKEL		
CONTACT MATERIAL	BRASS OR COPPER ALLOY		
CABLE TYPE	TPE, I8AWG, 300V		
CABLE JACKET COLOR	YELLOW		
BEND RADIUS	IO X DIAMETER		
R OF CONDUCTORS [AWG]	5x18 AWG		
SHIELDING	UNSHIEL	DED	
FLEX RATING	5 MILLION CYCLES (BASED ON IO TIMES CABLE OD)		
CABLE RATING	UL AWM, UV, OIL AND WATER RESISTANT, I8 AWG		
NGRESS PROTECTION	IP67, IP69K		
EMPERATURE RATING	-50°+105°C (-5	8° +221°F)	

			Sheet I Of I			
8	89R-R5HJRM-*	Size		Ver		
			889R-R5HJRM-*			
Drawn by: LNT	Date: 04/28/2014			0.0		