

6	7 8					
SP	ECIFICATIONS					
RTIFICATIONS	UL RECOGNIZED AND CSA CERTIFIED					
NG NUT MATERIAL	NICKEL PLATED BRASS					
R OVERMOLD MATERIAL	OIL RESISTANT PUR					
ITACT PLATING	GOLD OVER NICKEL-PLATED BRASS					
TACT MATERIAL	BRASS OR COPPER ALLOY					
CABLE TYPE	PVC, 24AWG, 300V					
E JACKET COLOR	BLACK					
END RADIUS	IO X DIAMETER					
F CONDUCTORS [AWG]	4X24 AWG (PICO MALE), 4X24 AWG (PICO FEMALE)					
SHIELDING	UNSHIELDED					
ABLE RATING	UL CM AWM STYLE 2661 VW-1 105C 300V, CSA AWM A/B 1/11 105C 300V FTI					
ISS PROTECTION	I P 6 7					
RATURE RATING	$-20^{\circ} \dots + 105^{\circ} C (-4^{\circ} \dots + 221^{\circ} F)$					

					R REFERENCE ONLY A 'www.ab.com/catalo	
Rockwell Automation			CONFIDENTIAL AND PROPRIETARY INFORMATION. THIS DOCUMENT CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF ROCKWELL AUTOMATION, INC. AND MAY NOT BE USED, COPIED OR DISCLOSED TO OTHERS, EXCEPT WITH THE AUTHORIZED WRITTEN PERMISSION OF ROCKWELL AUTOMATION, INC.			
_			Sheet I Of I			
889P-F4BBPM-*			Size		Ver	
Drawn by: LNT Date: 03-05-201		-2015	C		889P-F4BBPM-*	0.0
			·			