



- NOTES:  
 1. BOX CAN BE ROTATED IN 90° STEPS.  
 2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.  
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

FR.	C	B	BS	2F	2FF	FOOT HOLE MOUNTING QTY.
213T	18.22	7.00	2.75	-	5.50	4
						F1 OR F2

**Rockwell Automation**

TITLE OUTLINE  
213-15T FR. - BB - TEFC

NO.	11	UPDATED DRAWING	TJW	04/30/2007	TOLERANCES UNLESS SPECIFIED	DRAWN	PGK	07-29-1997
	10	REVISED TOL. WAS 5.22/5.16 NOW 5.25/5.19	RJW	05-01-2006	DEC.	CHK	ML	08-07-1997
	9	ADDED FOOT HOLE QTY. & MTG. TO TABLE CN 37322	TAT	01-14-2004	ML	APPD	PH	08-11-1997
	8	REMOVED NOTE 'SEE FRAME WHEN REQ'D'	DRS	04-23-2001	.XX ±.1	SCALE	7-32	
	8	FROM GROUND HOLE CN 29200-1698			.XX ±.03	REF		
	7	UPDATED C' BOX GEOMETRY CN 28426	HLB	11-10-2000	.XXX ±.005	FMF		
		REVISION			.XXXX ±.0005	PREV		
		BY & DATE	CHK	ANG	±.750"			
		MOUNTING	RFP					
		4	DIST	LB				

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT.