



- NOTES:
1. BOX CAN BE ROTATED ON ITS AXIS.
 2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°
 3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR

(B-SS200158)

FRAME	B	C	2F	BS
254T	10.25	23.52	8.25	4.12

Rockwell Automation		TOLERANCES UNLESS SPECIFIED		DRAWN KL 01-13-1994	
6	ADDED F2 VIEW MUR5891	RJW 05-22-2008	ML	CHK	ML 01-14-1994
5	REDRAWN IN AUTOCAD	TAT 06-29-2004	ML	APPD	JL 01-17-1994
4	REMOVED NOTE ABOUT IEEE-841	CN 2400-916	MJD 09-30-1997	SCALE	1=4
3	CLARIFIED NOTE & FOR IEEE SPC ONLY CN 21725-1158	MH 12-10-1996	XX ±.03	TITLE	OUTLINE
2	3/8-16UNC-2B WAS 1/4-20 & ADDED T TO CONDUIT BOX SIDE	RM 03-25-1994	XXX ±.005	REF	250 FR. - BB - TS - STD.
NO.	REVISION	CN 17609	XXXX ±.0005	FINISH	
	BY & DATE	CHK	ANG	PREV	
	REVISION	RFP	ANG	PREV	
	THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR PRODUCTS. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT	DIST	LB	SIZE	DRAWING NO. PAGE OF
					SS203002 6