



- NOTES:
1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
  2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
  3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

(B-SS504698)

CONDUIT BOX DIMENSIONS			
FRAME	AB	AC	OW
404	18.78	15.25	29.66
405	19.78	16.25	30.66

**Rockwell Automation**

TITLE OUTLINE - TAPPED LEAD HOLE  
400TS/US FR. - TEFC - STD.

UNITS: INCHES  
DEC. ±.1  
TOL. ±.03  
FIN. ±.008  
MATERIAL: 3000 ±.006  
FINISH: ANGLE ±7.30°

CHK: ANG  
APPD: M.L. 06-20-1988  
SCALE: .17=1  
REV: 7

NO.	REVISION	BY & DATE	CHK	ANG	±7.30°	REV.
7	UPDATED FRAME & ADDED 404 INFO	KL 10-25-2005	KL	10-25-2005	KL	10-25-2005
6	REDRAWN IN AUTOCAD	TAT 06-29-2004	TAT	06-29-2004	TAT	06-29-2004
5	ADDED NEMA 'C' DIM.	MFB 09-12-1998	MFB	09-12-1998	MFB	09-12-1998
4	REDRAWN ON CADD	TLB 06-19-1988	TLB	06-19-1988	TLB	06-19-1988

THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK. ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED. THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT.

405TS	16.25	34.12	13.75	6.88
-------	-------	-------	-------	------

FRAME	B	C	2F	BS
405TS	16.25	34.12	13.75	6.88